

Contak Premium

Version: may-19

Contak is an adhesion bridge that provides a mechanical grip to plaster mortars and adhesives on a smooth surfaces such as glass, ceramic, metals, wood, cement, etc.

PRODUCT DESCRIPTION

Features:

Excellent adherence bridge.
Mechanical grip for plastering.
Suitable for all types of surfaces.
Quick and easy application.
Tough and long-lasting.
Excellent flexibility. Not cracking.
Suitable for interiors and exteriors.

Technical properties:

Specific weight	1.27 ± 0.05 g/cm ³
pH	8.5 ± 1
Viscosity	120 ± 5 U.K.
Solid content	63 ± 5 %
Nature	Mineral particles in an acrylic emulsion
Appearance	Dense red liquid
Finish	Granular

Yield:

7-9 m²/l/coat. It depends on the type and condition of the substrate. The exact consumption must be determined by the means of a sampling of the work.

Format:

Available in pots of 1 l, 4 l, 12.5 l, 15 l.

Storage:

Keep in original pack, closed and in a cool and dry place. Keep from freezing and avoid direct sun exposure. Unopened, it may be conserved for at least 36 months from the date of manufacture. The product may thicken without losing its properties; shake/mix well before use.

APPLICATINO INSTRUCTIONS

Application surfaces:

Especially suitable on surface without porosity and / or mechanical grip such as glass, ceramic, metals, wood, concrete smooth, etc. Do not apply on substrate with humidity.

Conditions of the substrate:

The substrate must be dry, firm, well-adhered and free from any impurities that may hinder the product from setting fully.

Preparation of the substrate:

If the substrate presents any remaining dust, grease, dirt and other impurities, it is recommended to do a thorough cleaning to ensure adequate adhesion.

If the substrate is not well adhered, first remove areas that do not adhere by scraping and brushing.

Application method:

Mix well to ensure a even consistency and apply one coat spreading adequately.

Drying:

24 hours at 25 °C and 60% relative humidity.

Environmental conditions:

The working temperature (ambient and support) must be between +5 ° C and +32 ° C. Avoid applying when the ambient relative humidity is higher than 80% or when there is a probability of dew and condensation. Do not apply with direct incidence of the sun, in overheated supports or rain forecast.

Tools:

Roller and brush.

Tool cleaning:

Clean tools after use with warm water.

Notes

The mineral substrate must be at least 28 days old, be cured and dry.

Do not apply on surfaces with standing water or in permanent contact with water.

It is recommended to protect the treated surface from rain until plastering.

The parts that are not going to be treated must be protected (glass, wood, etc.).

Do not mix with other products or specific properties may change.

ADDITIONAL INFORMATION

Usage warnings:

None in particular for normal use and people who do not have special pathologies. Alkaline product, you should protect skin and eyes especially. In case of contact with the eyes: rinse carefully with water for several minutes, remove contact lenses when they are present and can be done easily, continue with the wash. Apply with good ventilation, do not inhale product. Keep out of reach of children.

Waste management:

According to local legal provisions. The pots are made of recycled polypropylene. Help protect the environment, do not throw waste through the drain and use the nearest recycling centre.

Responsible gesture:

Minimize the product waste by estimating the amount you will need. Recover the unused product to give it a new use, keep it under the Storage section.

Safety information:

For information regarding safety, physical, ecological and toxicological information see the latest version of the product's Material Safety Data Sheet.

Technical advice:

For further information, please contact with local distributor or manufacture (technicalsupport@graphenstone.com).

The information provided is given in good faith, based on current knowledge and IEdiSA's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of IEdiSA. The Technical Specifications sheet is useful for information and consulting but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Any modification to the instructions and recommendations by the user, he will assume all the corresponding risk and responsibility. IEdiSA reserves the right to modifications that improve the product or its application. This version invalidates previous ones.